New Product Notice

January 2020

X9D On-Car Brake Lathe Package

Model No. PCIX9DC3ADPH

THE NEW PFM X9D brings a bundle of Pro-Cut exclusive advanced technology to the job. With simple user facing controls, sophisticated job tracking, maintenance alert system, and a smoother running, variable speed DC drive-train, the X9D will return years of continuous brake service profits for your shop!

Features:

- VARIABLE SPEED to tackle modern vehicle platforms with all-wheel drive with ease
- ADVANCED 2.0 ELECTRONICS PLATFORM with ROI tracking, maintenance alerts, and full compatibility with our latest digital upgrades: G2X and GYR
- **PERFORMANCE PLUS CUTTING HEAD** with robust T-nut locking system, 92 mm tool arms for larger performance rotors, and click-n-lock depth knobs for accuracy
- **FASTER COMPENSATION** and better accuracy with times averaging less than 15 seconds and lateral run-out under .001"
- **DC MOTOR** delivers smooth, clean, and consistent power for a factory approved finish every time
- **SUPER BRIGHT WORK LIGHT** with 6 LEDs mounted where you need it for safe, efficient operation
- UNMATCHED 2 YEAR WARRANTY allows you to machine rotors day in and day out with peace of mind that goes well beyond achieving your ROI!
- AWARD WINNING SERVICE TEAM includes live tech assistance and trained and stocked professional local reps to keep you up and running

Specifications:

Minimum Rotor Thickness:0.2"Maximum Rotor Diameter:16.4"Maximum Friction Face:3.62"Maximum Depth of Cut:0.015" / sideMotor:1.25 HPShipping Weight:200 lbs.Electrical Supply:110v/60Hz or 220v/50Hz compatibleFeed Distance:6.70" (7.44" Opt.)Working Height Range:21" - 43"Variable Spindle Speed:46 RPM - 115 RPMFeed Rate:0.005" / rev.	Maximum Rotor Thickness:	1.75"
Maximum Friction Face:3.62"Maximum Depth of Cut:0.015" / sideMotor:1.25 HPShipping Weight:200 lbs.Electrical Supply:110v/60Hz or 220v/50Hz compatibleFeed Distance:6.70" (7.44" Opt.)Working Height Range:21" - 43"Variable Spindle Speed:46 RPM - 115 RPM	Minimum Rotor Thickness:	0.2"
Maximum Depth of Cut:0.015" / sideMotor:1.25 HPShipping Weight:200 lbs.Electrical Supply:110v/60Hz or 220v/50Hz compatibleFeed Distance:6.70" (7.44" Opt.)Working Height Range:21" - 43"Variable Spindle Speed:46 RPM - 115 RPM	Maximum Rotor Diameter:	16.4"
Motor:1.25 HPShipping Weight:200 lbs.Electrical Supply:110v/60Hz or 220v/50Hz compatibleFeed Distance:6.70" (7.44" Opt.)Working Height Range:21" - 43"Variable Spindle Speed:46 RPM - 115 RPM	Maximum Friction Face:	3.62"
Shipping Weight:200 lbs.Electrical Supply:110v/60Hz or 220v/50Hz compatibleFeed Distance:6.70" (7.44" Opt.)Working Height Range:21" - 43"Variable Spindle Speed:46 RPM - 115 RPM	Maximum Depth of Cut:	0.015" / side
Electrical Supply:110v/60Hz or 220v/50Hz compatibleFeed Distance:6.70" (7.44" Opt.)Working Height Range:21" - 43"Variable Spindle Speed:46 RPM - 115 RPM	Motor:	1.25 HP
Feed Distance:6.70" (7.44" Opt.)Working Height Range:21" - 43"Variable Spindle Speed:46 RPM - 115 RPM	Shipping Weight:	200 lbs.
Working Height Range:	Electrical Supply:	110v/60Hz or 220v/50Hz compatible
Variable Spindle Speed: 46 RPM - 115 RPM	Feed Distance:	6.70" (7.44" Opt.)
	Working Height Range:	21" - 43"
Feed Rate: 0.005" / rev.	Variable Spindle Speed:	46 RPM - 115 RPM
	Feed Rate:	0.005" / rev.



\$12,313.00

Price and product information are subject to change without notice.





We offer two convenient ways to order:

- To order online, log into iN. Navigate to SERVICE > Service Bay > Tool and Equipment Program, then search by model number.
- To order by phone, call 1-888-424-6857.
 Customer service representatives are available from 7:30 AM until 7:00 PM CT, Monday through Friday.

Supplied by: Pro-Cut International

Alignment, Wheel, and Brake Equipment On-Car Brake Lathes and Accessories

Includes:

	X9D on-car brake lathe and fixed post trolley
	DRO computer box (accepts G2X/GYR upgrades)
PCI50220	Speed-Lock cutting head
PCI503ADPH0	Honda/Acura 3 Piece Adapter Package
PCI50996	4 Lug Honda/Acura Adapter, Red label (56 mm / 4 x 100 mm)
PCI50997	5 Lug Honda/Acura Adapter, Blue label (64 mm / 5 x 114.3 mm & 120 mm)
PCI50998	4 & 5 Lug Honda/Acura Adapter, Yellow label (70 mm / 5 x 114.3 mm & 4 x 114.3 mm)
PCI50ACCHON	Honda/Acura Accessory Kit
PCI503MSC	COTC Brake Hub Cleaning Kit
PCI50742	Silver Cutting Bits - 10 Piece
PCI37034	Pair of S Hooks
PCI50703	Chip Deflector (Standard)
PCI50754	Chip Deflector (Heavy-Duty)
PCI50729	Brake Specifications Guide
PCI50752	Lathe Cover
Options:	
PCI501200UPG	G2X Upgrade Package** \$1,531.00
	Upgrades Basic Lathe to DRO G2X with live run-out and thickness measurement. Includes GYR cutting head with measurement unit, GPM module, and all necessary cables.
	**The G2X (PCI501200UPG) Upgrade Package will not plug and play with lathes sold before 01/01/12.
PCI501360	GYR Upgrade Package*** \$1,536.00
	Upgrades DRO G2X to full GYR with live feedback and computer direction and reporting. Includes scanner, tablet, tablet holder, and GYR application.
	***Requires G2X Upgrade Package. To continue the vehicle data and system updates after the first year there is a \$395 annual license fee charged by Pro-Cut directly. The charges will be billed on the anniversary of the original purchase date of the brake lathe. The GYR (PCI501360) Upgrade Package will not plug and play with lathes sold before 01/01/12.

Warranty:

Two year warranty

Price and product information are subject to change without notice.

Supplied by: Pro-Cut International

Alignment, Wheel, and Brake Equipment On-Car Brake Lathes and <u>Accessories</u>

We offer two convenient ways to order:_____

- To order online, log into iN. Navigate to SERVICE > Service Bay > Tool and Equipment Program, then search by model number.
- To order by phone, call 1-888-424-6857. Customer service representatives are available from 7:30 AM until 7:00 PM CT, Monday through Friday.